



Labelase® 28100 Printer

Power to match the demands of high speed production lines



Labelase® 28100 Specifications

Dimensions	55 x 27 x 15 in (140 x 69 x 38 cm)
Net Weight	190 lbs (< 86 kg)
Power	120 or 240 VAC, 50/60 Hz, 7A
Tag Feed	300 ft (91 m) continuous roll
Data Input	Local or network
Maximum bar code length	Per customer specs.
Tag Width	3.0 in (76 mm) or 4.0 in (102 mm)
Bar Codes Per Tag	Unlimited, within available space
Bar Code Symbologies	Supports most common 1D/2D bar codes. Custom or proprietary symbologies can be developed
Tag Composition	InfoSight metal tags with laser-markable coatings
Communications Interface	PC to Printer: RS232C Serial, USB or Ethernet Host to PC: InfoSight Extended Protocol, File Transfer Protocol
Tag Layout Software	Producer™ software included free. Windows Compatible: 7- 8 (32/64 bit), or (32/64 bit)

High Speed, Harsh Environments - Durability and High Volumes

The 28100 printer takes high-speed metal tag printing onto the mill floor and into the heart of industrial production lines.

The LL28100 offers user-friendly versatility with PC-driven fonts and bar codes.

- ◆ 100 watt laser — the world's fastest industrial tag printing.
- ◆ Extra laser power for longer, wider tags and more data.
- ◆ Automated printing from 300 foot coils. Compatible with automated taggers.
- ◆ Simple maintenance routines.
- ◆ One-year warranty and lifetime live 24/7 technical support at no extra charge.

