



LS-Tag™

Identification for Anatomical Specimens



InfoSight Tags are the industry standard laser-marked metal barcode tag.

LS-Tag™ Specifications:

Industry	Life Sciences, Education
Typical Customer	Anatomical Laboratories, Training Centers
Purpose	Identification for biological specimens through preservation process and educational investigation.
Resistance	Heat: -52°F (-47°C) to 1600°F (871°C) Chemical: Most acid washes; Long exposure to most organic solutions Abrasion: Moderate Ultraviolet: Highly resistant to sunlight and fading
Sizes	Width: 3.0 in (76.2 mm) Lengths: to customer specification, not less than 1.0 in (25.4 mm) Typical Lengths: 1 - 8 in (25.4 - 203mm)
Composition	Stainless Steel with high contrast laser-markable coatings
Available Forms	Print on-site with one of InfoSight's durable, laser metal tag printers or order pre-printed by InfoSight
Available Colors	Standard white, colors by special order

Identification and Security During Specimen Preservation

Specimens used in medical and scientific training are exposed to a wide spectrum of disinfectants, germicides, and preservatives. Some processes can last up to 6 months in refrigerated conditions.

LS-Tag complements InfoSight's PermaLabel® Tag. While PermaLabel resists abrasions that come with regular handling, LS-Tag is superior when specimens are exposed to formalin and glutaraldehyde for long periods, as well as chemicals and organic cleansers.

- ◆ 1-D and 2-D barcodes; plus human-readable text.
- ◆ Adaptable to most common attachment techniques.
- ◆ Compatible with all InfoSight printers; no consumables required.
- ◆ Processes vary. Call for sample tags and test LS-Tag in your facility.



Printers & Tags that Cut Costs, Increase Safety and Ensure Traceability