



SSL-Tag™

Lifetime Asset ID for Fixed and Mobile Assets



SSL-Tag™ Specifications:

Industry	Product oriented industry, for asset identification
Typical Customer	Any company with assets needing lifetime identification
Typical Use	Industrial kitchens, water reclamation, oil and gas production, chemical and electric power plants. Manufactured products used or installed out of doors. Construction, plant maintenance,
Resistance	Heat: 1100°F (593°C) Chemical: Moderate acids, caustics, solvents and organics Abrasion: Heavily resistant to weathering and moderately resistant to abrasion Ultraviolet: Highly resistant to sunlight and fading
Sizes	Width: 3.0 in (76 mm) Lengths: to customer specification, not less than 1.0 in (25 mm) Die-Cuts: available by special order
Composition	Stainless steel with high contrast laser markable coatings
Available Forms	Pre-printed by InfoSight or print on-site with one of InfoSight's durable, laser metal tag printers
Available Colors	Black print on bright stainless steel finish

Asset Identification with the Durability of Stainless Steel

SSL-Tag is a coil-fed, continuous print, stainless steel ID tag. With the luster of stainless steel SSL can withstand most common solvents and cleaners, as well as most weather conditions.

- ◆ Continuous batch printing for process efficiency.
- ◆ Immediately usable - no coatings or laminates.
- ◆ 430 ferric stainless steel survives where silk screened steel labels fail.
- ◆ Ribbons, ink and cartridges eliminated.
- ◆ Stainless steel finish for enhanced appearance.
- ◆ Adaptable to industrial adhesives.



Printers & Tags that Cut Costs, Increase Safety and Ensure Traceability