



InfoTag®

Industrial Tags for Product Identification



- For industrial applications with harsh environments
- Resistant to:
 - Heat—up to 1800°F (982°C)
 - Chemicals
 - Abrasion
 - UV Exposure
- 3" (76mm) Wide X Customized Length
- Metal substrate with laser markable coating

- ◆ Track Products Indoors and Out.
- ◆ Versatile barcode ready identification tag.
- ◆ Prevent mixed batches and lost products.
- ◆ Error free product movement through processes, inventory, shipping, and end use.
- ◆ Available nicked and notched.
- ◆ Printed on InfoSight LabelLase® Printers with high contrast alphanumeric characters, graphics, and 1D & 2D barcodes. →
- ◆ Preprinted tags available.



Find out how easy it is to design and print your tags with a LabelLase® Metal Tag Printer & free Producer™ Software.



PRINTERS & TAGS THAT CUT COSTS, INCREASE SAFETY, & ENSURE TRACEABILITY

InfoTag®

Technical Specifications

Industry	Industrial manufacturing, distribution
Typical Customer	Harsh environments: more durable than paper or plastic
Purpose	Rugged barcode ready identification - will not tear or detach during handling, processing and shipping
Resistance	<p>Heat: In excess of 1800°F (982°C)</p> <p>Chemical: Resistant to common solvents</p> <p>Abrasion: Moderate</p> <p>Ultraviolet: Highly resistant to sunlight and fading</p>
Sizes	<p>Width: 3.0 in (76 mm)</p> <p>Lengths: to customer specification, not less than 1.0 in (25 mm)</p>
Composition	Metal with high contrast laser-markable coatings
Available Forms	Print on-site with one of InfoSight's durable, laser metal tag printers or preprinted by InfoSight
Available Colors	Standard white; colors available



Technical specifications are subject to change without notice.
 Producer and "We Barcode Difficult Stuff" are trademarks of InfoSight.
 Labelase and InfoTag are registered trademarks of InfoSight.
 Copyright 2020 InfoSight Corporation