

KettleTag[®]PLUS EZ™

Tags for Fabricators and Galvanizers



- For Galvanizers and Fabricators
- Track pieces through entire galvanizing process
- Resistant to:
 - Heat—1000°F (538°C)
 - Chemicals—caustic & acid rinses, molten zinc bath
 - Abrasion
 - UV Exposure
- 3" Wide (76mm) X Customizable Length
- Metal substrate with laser markable coatings
- No Lamination required
- The only tag that survives all 9 steps for galvanizing listed by the American Galvanizers Association.
- Increase efficiency & reduce handling—tags are applied once and are readable throughout the process.
- Traceability & error proof installations.
- Printable with InfoSight LabeLase[®] Metal Tag Printers.
- Preprinted tags are available.



Find out how easy it is to design and print your tags with a LabeLase®

Metal Tag Printer & free ProducerTM

Software.



PROCESSES VARY—CALL TODAY TO TEST KETTLETAG PLUS IN YOUR PROCESS

KettleTag[®]PLUS EZ™

Technical Specifications

Industry	Metal galvanizing
Typical Customer	Galvanizers and fabricators
Purpose	Tracking work pieces through the entire galvanizing process
Resistance	Heat: 1000°F (538°C)
	Chemical: $180^{\circ}F$ ($82^{\circ}C$) in 20% H ₂ SO ₄ for 2 hours; or $100^{\circ}F$ ($38^{\circ}C$) 24% HCL for 2 hours.
	Abrasion: Moderate
	Ultraviolet: Highly resistant to sunlight and
Sizes	Width: 3.0 in (76 mm) Lengths: to customer specification, not less than 1.0 in (25 mm) Typical Lengths: 3.0 in (76 mm)
Composi-	Metal with high contrast laser-markable coatings
Available Forms	Print on-site with one of InfoSight's durable, laser metal tag printers or pre-printed by InfoSight.
Available Colors	White and Yellow



Scan the QR Code to learn more about our Fabricator tags:

