

Embed-a-Tag™

Concrete Casting ID Tags



- For precast concrete products applications
- Resistant to:
 - Heat: 1000°F (538°C)
 - Chemical
 - Abrasion
 - UV Exposure
- 3" Wide (76mm) X Customized Length
- Metal with laser markable coating

Embed-A-Tag™ provides permanent, durable identification for precast concrete with lifetime traceability.

- Tags mount flush to top, facings, or edges.
- Use adhesive to hold tag on form during pour OR insert into wet concrete.
- Curing permanently attaches tag to the casting.
- Better than chalk that wipes off and paper tags that tear or fall off.
- Tag remains readable after long term outdoor exposure and will not rust.
- Compatible with InfoSight's LabeLase® Printers.
- Preprinted tags are available.



Find out how easy it is to design and print your tags with a LabeLase® Metal Tag Printer & free Producer™ Software.

Printers & Tags that cut costs, increase safety, & ensure traceability

InfoSight Corporation
20700 US Hwy 23
Chillicothe, OH 45601 USA

Tel: +1 740-642-3600
sales@infosight.com
www.infosight.com



Embed-a-Tag™

Technical Specifications

Industry	Precast/pre-stressed concrete
Typical Customer	Precast concrete plants
Purpose	Durable, weather proof identification for flush mounting on top or edges of precast concrete members
Resistance	Heat: 1000°F (538°C)
	Chemical: Highly rust resistant Moderate resistance to common chemicals
	Abrasion: Moderate
	Ultraviolet: Highly resistant to fading
Sizes	Width: 3.0 in (76 mm) Lengths: to customer specification, not less than 1.0 in (25 mm) Typical Length: 6.0 in (152 mm)
Composition	Stainless Steel with high contrast laser-markable coatings and ceramic coatings on both sides
Available Forms	Print on-site with one of InfoSight's durable, laser metal tag printers or preprinted by InfoSight
Available Colors	White, colors by special order

